PEUGEOT 308 T7 308 1.6 16V VTI THP (115 KW) 5FV (2009-2011)



ENGINE EP6CD1 Capacity: 4,25 liter, Filter capacity: 0,25 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Avanza MSP 0W-30			
Change every 30000 km/24 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
Avanza MSP 0W-30			
Change aver 20000 km/ 10 months			

Change every 20000 km/ 12 months

	TRANSAXLE AUTOMATIC AL4 4/1 Capacity: 5,85 liter (Dry fill), Capacity: 3 liter (Service fill)			
USE CLIMATE				
Normal Moderate)			
PRODUCT RECOMMENDATION 1				
SP Matic 2032				

TRANSAXLE MANUAL BE4R 5/1 Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	•

PEUGEOT 308 T7 308 1.6 16V VTI THP (115 KW) 5FV (2009-2011)



ELECTRO-HYDRAULIC POWER STEERING (EHPS)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Fluid 3013			

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Change every 120000 km/ 48 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.