

PEUGEOT 309 309 1.1 (1985-1988)

ENGINE E1A
Capacity: 3,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 2
Emperol 5W-40

PRODUCT RECOMMENDATION 3
Asyntho 5W-30

Check every 3000 km, change every 10000 km/ 12 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 2
Emperol 5W-40

PRODUCT RECOMMENDATION 3
Asyntho 5W-30

Change every 5000 km/ 6 months

TRANSAXLE MANUAL 4/1
Capacity: 2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
SP Gear 5015

PRODUCT RECOMMENDATION 2
Gearlube RPC 75W-80

Check every 60000 km

HYDRAULIC BRAKE SYSTEM

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2
Drauliquid-S DOT 4

Check every 10000 km/ 12 months, change every 40000 km/ 24 months

COOLING SYSTEM
Capacity: 6,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Coolant -38 Organic NF

Change every 120000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.