

PEUGEOT PARTNER TEPEE B9 PARTNER TEPEE 1.6I 16V VTI 5FS (2012-2016)

**ENGINE EP6**

Capacity: 4,25 liter, Filter capacity: 0,25 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

TRANSAXLE MANUAL MA 5/1

Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Check every 24 months/ 30000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

*Check every 20000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 30000 km, change every 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 20000 km, change every 24 months

PEUGEOT PARTNER TEPEE B9 PARTNER

TEPEE 1.6I 16V VTI 5FS (2012-2016)



ELECTRO-HYDRAULIC POWER STEERING (EHPS)

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 24 months/ 30000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 20000 km/ 12 months

HYDRAULIC POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

COOLING SYSTEM

Capacity: 5,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 24 months/ 30000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.