

ENGINE MA1.04 Capacity: 10,1 liter (Dry fill), Capacity: 7,5 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

Change every 30000 km/ 24 months

TRANSAXLE MANUAL G91.00 / ZF S7-45HL 7/1 Capacity: 3,2 liter, Capacity: 3,3 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 180000 km/ 144 months

TRANSMISSION SEMI-AUTOMATIC CLU Capacity: 5,2 liter	TCH PART CG1.05 / ZF 7DT45	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 180000 km/ 144 months		

TRANSMISSION SEMI-AUTOMATIC TRANSMISSION PART CG1.05 / ZF 7DT45 7/1 Capacity: 3 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	

Change every 180000 km/ 144 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change avenu 21 months		6

Change every 24 months



COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 12 EVO	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.