

# PORSCHE (EU) 911 993 911 TURBO (1995-1998)

**ENGINE M64.60**

Capacity: 9 liter, Capacity: 11,5 liter (Initial fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>

*Change every 20000 km/ 12 months*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Emperol 5W-40</b>	<b>Emperol 5W-50</b>	

*Change every 20000 km/ 12 months***DIFFERENTIAL FRONT**

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

*Check every 20000 km/ 12 months, change every 80000 km***TRANSAXLE MANUAL G64.51 6/1**

Capacity: 4,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

*Check every 20000 km/ 12 months, change every 80000 km***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid Racing</b>		

*Check every 20000 km, change every 24 months*

**PORSCHE (EU) 911 993 911 TURBO (1995-1998)****HYDRAULIC CLUTCH (CHF CAP)**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

*Check every 20000 km/ 12 months*

**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

*Check every 20000 km/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*