

PORSCHE (EU) 911 997 911 TARGA 4 (2008-2012)



ENGINE MA1.02
Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 2

Helar 0W-40

PRODUCT RECOMMENDATION 3

Emperol 5W-40

Change every 30000 km/ 24 months

DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

TRANSAXLE MANUAL G97.05 / G97.35 6/1

Capacity: 2,9 liter (Dry fill), Capacity: 2,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Change every 180000 km/ 144 months

TRANSMISSION SEMI-AUTOMATIC CLUTCH PART CG1.30 / ZF 7DT45

Capacity: 5,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072

TRANSMISSION SEMI-AUTOMATIC TRANSMISSION PART CG1.30 / ZF 7DT45 7/1

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PORSCHE (EU) 911 997 911 TARGA 4 (2008-2012)**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 24 months/ 30000 km

POWER STEERING

Capacity: 1,27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 29-32 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 12 EVO	

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.