

PORSCHE (EU) BOXSTER 986 BOXSTER

(1996-1999)

**ENGINE**

Capacity: 8,3 liter, Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Specialsynth MSP 5W-40****PRODUCT RECOMMENDATION 2****Helar 0W-40****PRODUCT RECOMMENDATION 3****Emperol 5W-40***Change every 20000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 0,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90***Check every 20000 km/ 12 months, change every 160000 km***TRANSAXLE MANUAL G86.00 / G86.01 5/1**

Capacity: 2,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90***Check every 20000 km/ 12 months, change every 160000 km***TRANSMISSION AUTOMATIC Tiptronic A86.00 / A86.05 / A86.20 5/1**

Capacity: 9,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032***Check every 20000 km/ 12 months, change every 160000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid Racing***Change every 24 months*

PORSCHE (EU) BOXSTER 986 BOXSTER

(1996-1999)



HYDRAULIC CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid Racing

Check every 20000 km, change every 24 months

POWER STEERING

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 17 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.