

PORSCHE (EU) CAYENNE 9PA CAYENNE GTS (2008-2010)

**ENGINE M48.01**

Capacity: 8,5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

Change every 30000 km/ 24 months

DIFFERENTIAL FRONT (4x4)

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 240000 km/ 192 months

DIFFERENTIAL REAR (4x4)

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 240000 km/ 192 months

DIFFERENTIAL REAR LIMITED SLIP (4x4)

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear LS 1015		

Change every 240000 km/ 192 months

TRANSFERBOX

Capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1081		

Change every 240000 km/ 192 months

PORSCHE (EU) CAYENNE 9PA CAYENNE GTS (2008-2010)


TRANSMISSION AUTOMATIC Tiptronic A48.02 6/1

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 240000 km/ 192 months*
TRANSMISSION MANUAL G48.02 6/1

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 240000 km/ 192 months*
HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,95 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*
POWER STEERING

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 60000 km/ 24 months*
COOLING SYSTEM

Capacity: 18-21 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Check every 24 months/ 30000 km*

PORSCHE (EU) CAYENNE 9PA CAYENNE GTS (2008-2010)

**PORSCHE DYNAMIC CHASSIS CONTROL (PDCC)**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 48 months/ 60000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.