PROTON INSPIRA INSPIRA 2.0 P3-90A (2011 AND AFTER)



SE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 20000 km/ 12 month	ns	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Presteza MSP 0W-30	Avanza MSP 0W-30
Change every 20000 km/ 12 month	าร	
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 10000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Presteza MSP 0W-30	Avanza MSP 0W-30
Change every 10000 km		·
TRANSAXLE CVT F1CJA 1/1		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4016		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	ax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Check every 20000 km/ 12 months, cha	ange every 40000 km/ 24 months		

PROTON INSPIRA INSPIRA 2.0 P3-90A (2011 AND AFTER)



01 1 000001 / 10 11 1	100001 /04	•
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)		

Check every 20000 km/12 months, change every 40000 km/24 months

POWER STEERING Capacity: 1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Matic 2032	ATF Almirol	ATF Dexron II-D	

JSE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 20000 km/ 12 months, change every 120000	km/ 72 months
JSE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

AIRCONDITIONING SYSTEM Capacity: 480-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.