

RENAULT (EU) 19 X53 19 1.4 (59 KW) X53 (1988-1995)



ENGINE E6F, E7F
Capacity: 4 liter, Filter capacity: 0,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-50

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Check every 3000 km, change every 10000 km/ 12 months

TRANSAXLE AUTOMATIC MB1 3/1
Capacity: 2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Change every 50000 km/ 36 months

TRANSAXLE MANUAL JB0 4/1
Capacity: 3,25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

Check every 10000 km/ 12 months, change every 50000 km/ 36 months

TRANSAXLE MANUAL JB1 5/1
Capacity: 3,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

Check every 10000 km/ 12 months, change every 50000 km/ 36 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Change every 50000 km/ 36 months

PRODUCT RECOMMENDATION

RENAULT (EU) 19 X53 19 1.4 (59 KW) X53 (1988-1995)



HYDRAULIC BRAKE SYSTEM ABS

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 50000 km/ 36 months

COOLING SYSTEM

Capacity: 5,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 50000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.