RENAULT (EU) CLIO IV X98 CLIO IV 1.5 DCI 75 (2012-2018)



ENGINE K9K Capacity: 4,5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40		
Change every 30000 km/ 12 months				
USE		CLIMATE		
Alternative (acceptable)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40		
Change every 20000 km/ 12 months				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40		
Change every 30000 km/ 24 months	•	·		

TRANSAXLE MANUAL JR5 5/1 Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid-LV Super DOT 4			
Change every 120000 km/ 36 months			

RENAULT (EU) CLIO IV X98 CLIO IV 1.5 DCI 75 (2012-2018)



COOLING SYSTEM Capacity: 5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 16			

Change every 150000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.