

RENAULT (EU) KANGOO FAMILY II K61

KANGOO FAMILY II 1.6 16V ECO 2 (2008-2013)



ENGINE K4M
Capacity: 4,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Meganza MSP 5W-30	Avanza RPC 5W-30

Change every 30000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Meganza MSP 5W-30	Avanza RPC 5W-30

Change every 15000 km/ 6 months

TRANSAXLE AUTOMATIC DP0 4/1
Capacity: 6 liter (Dry fill), Capacity: 3,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

TRANSAXLE AUTOMATIC DP2 4/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 12 months/ 30000 km

TRANSAXLE MANUAL JR5 5/1
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

Check every 12 months/ 30000 km

RENAULT (EU) KANGOO FAMILY II K61

KANGOO FAMILY II 1.6 16V ECO 2 (2008-2013)

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 30000 km/ 12 months, change every 24 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 12 months/ 30000 km

COOLING SYSTEM

Capacity: 5-5,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.