

RENAULT (EU) KOLEOS H45 KOLEOS 2.0 DCI (127 KW) 4X4 (2008-2016)

**ENGINE M9R**

Capacity: 7,4 liter (Service fill), Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40

Change every 30000 km/ 12 months

DIFFERENTIAL (4x4)

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Gearlube LS 80W-90	

TRANSAXLE AUTOMATIC AJ8 6/1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

TRANSAXLE MANUAL ND5 6/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

TRANSAXLE MANUAL ND8 6/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

RENAULT (EU) KOLEOS H45 KOLEOS 2.0 DCI (127 KW) 4X4 (2008-2016)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 12 months/ 30000 km

COOLING SYSTEM

Capacity: 7,9 liter (+ automatic transmission/transaxle), Capacity: 7,5 liter (+ manual transmission/transaxle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 16

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.