RENAULT (EU) SAFRANE X54 SAFRANE 3.0 V6 X54 (1992-1996)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-50	Asyntho 5W-30

Check every 3000 km, change every 10000 km/ 12 months

DIFFERENTIAL FROM AUTOMATIC AD Capacity: 1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Change every 50000 km	<u>'</u>

TRANSAXLE MANUAL PK1 5/1 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Charles a remained a character and a second	00001	ı

Check every 20000 km, change every 50000 km

TRANSAXLE MANUAL PK7 5/1 Capacity: 3,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Check every 20000 km, change every 50	

TRANSMISSION AUTOMATIC AD8 4/1
Capacity: 4 liter

USE

Normal

PRODUCT RECOMMENDATION 1

ATE Devrop II-D

ATF Dexron II-D

Change every 50000 km

RENAULT (EU) SAFRANE X54 SAFRANE 3.0 V6 X54 (1992-1996)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 40000 km/48 months

POWER STEERING Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 1000 km/ 12 months	

COOLING SYSTEM Capacity: 10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 80000 km/ 48 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo