RENAULT (EU) SCÉNIC III J95 SCÉNIC III 1.2 TCE 130 (2013-2016)



| ENGINE H5F Capacity: 4,6 liter | | |
|-----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Flexible (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar MSP+ 5W-40 | Specialsynth MSP 5W-40 | Helar 0W-40 |

Change every 30000 km/24 months

| TRANSAXLE MANUAL TL4 6/1 Capacity: 1,9 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 5015 | Gearlube RPC 75W-80 | | |
| | | | |

| HYDRAULIC BRAKE SYSTEM ABS Capacity: 0-0 liter (Between min and max.) | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-LV Super DOT 4 | | |
| | ' | |

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

| COOLING SYSTEM Capacity: 6,5 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 16 | |

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

AIRCONDITIONING

Capacity: 480 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.