RENAULT (EU) VEL SATIS B73 VEL SATIS 2.0 16V TURBO B73 (2005-2007)



ENGINE F4R Turbo Capacity: 5,4 liter, Filter capacity: 0,15 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30		
Change every 20000 km/ 12 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30		
Change every 10000 km/ 6 months				

TRANSAXLE AUTOMATIC Aisin Warner SU 1 5/1 Capacity: 7,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				
Check every 10000 km	'			

TRANSAXLE MANUAL PK6 6/1 Capacity: 2,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

HYDRAULIC BRAKE SYSTEM ABS Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 20000 km/ 12 months, change every 120000 ki	m/ 48 months

RENAULT (EU) VEL SATIS B73 VEL SATIS 2.0 16V TURBO B73 (2005-2007)



POWER STEERING Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 20000 km/ 12 months	

COOLING SYSTEM Capacity: 6,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	

Check every 20000 km/12 months, change every 120000 km/48 months

AIRCONDITIONING Capacity: 650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 265 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.