SAAB 9-2X 9-2X 2.5 (2004-2005)



ENGINE Capacity: 4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Asyntho 5W-30	Emperol 10W-40		
		·	

Change every 12000 km/ 12 months

DIFFERENTIAL FROM AUTOMATIC		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Check every 48000 km/ 30 months		·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Check every 48000 km/30 months

Check every 48000 km/30 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80
Check every 48000 km/ 30 months		

Check every 48000 km/30 months

SAAB 9-2X 9-2X 2.5 (2004-2005)



TRANSAXLE AUTOMATIC 4/1 Capacity: 9,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Chack avany 19000 km/ 20 months			

Check every 48000 km/ 30 months

TRANSAXLE MANUAL 5/1 Capacity: 3,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Check every 48000 km/30 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

Check every 48000 km/30 months

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 48000 km/30 months

HYDRAULIC CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 48000 km/ 30 months		

SAAB 9-2X 9-2X 2.5 (2004-2005)



POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 48000 km/ 30 months		·

COOLING SYSTEM Capacity: 7 liter, Capacity: 6,9 liter (with automatic transmission)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Check every 48000 km/ 30 months	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.