SAAB 9-3 CABRIOLET 9-3 CABRIOLET 1.9 TID (110 KW) (2004-2011)



ENGINE Z19DTH Capacity: 4,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC AF 40 6/1 Capacity: 7 liter (Dry fill), Capacity: 2,85 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
01 1 000001 / 10 11	1000001 (70 11	:

Check every 30000 km/12 months, change every 120000 km/72 months

TRANSAXLE MANUAL F40 6/1 Capacity: 2,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Charle avenue 12 months / 20000 lem		'	

Check every 12 months/ 30000 km

HYDRAULIC SYSTEM ROOF Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0,43 liter (L.H.D.), Capacity:			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 30000 km/12 months ch	ango overy 18 months	:	

Check every 30000 km/ 12 months, change every 48 months

SAAB 9-3 CABRIOLET 9-3 CABRIOLET 1.9 TID (110 KW) (2004-2011)



POWER STEERING Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 12 months/ 30000 km	

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 12 months/ 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.