

SAAB 9-3 SPORT 9-3 SPORT 2.0T (129 KW) (2002-2011)

**ENGINE B207L**

Capacity: 6,75 liter (Initial fill), Capacity: 6 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40

*Change every 30000 km/ 12 months***TRANSAXLE AUTOMATIC FA 57 5/1**

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Check every 30000 km/ 12 months, change every 120000 km/ 72 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

*Check every 12 months/ 30000 km***TRANSAXLE MANUAL F40 6/1**

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

*Check every 12 months/ 30000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 0,43 liter (L.H.D.), Capacity: 0,37 liter (R.H.D.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 30000 km/ 12 months, change every 48 months

SAAB 9-3 SPORT 9-3 SPORT 2.0T (129 KW) (2002-2011)



POWER STEERING

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 12 months/ 30000 km

COOLING SYSTEM

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.