SAAB 9-5 9-5 2.0T (2010-2011)



| | CLIMATE |
|--------------------------|--------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar MSP+ 5W-40 | Specialsynth MSP 5W-40 |
| | |

Change every 30000 km/ 12 months

| TRANSAXLE AUTOMATIC AF 40-6 6/1 Capacity: 0-0 liter (Between min and max.) | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |
| Change every 120000 km/ 72 months | ' | |

| TRANSAXLE MANUAL F40-6 6/1 Capacity: 2,4 liter (Dry fill), Capacity: 2,2 liter (Service fill) | | | | |
|---|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| SP Gear 1011 | SP Gear 5015 | Syngear TDL 75W-90 | | |
| Check every 12 months/ 30000 km | , | | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0-0 liter (Between min and max.) | | |
|--|--|---------------------|
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Drauliquid-LV Super DOT 4 | | |

Check every 30000 km/ 12 months, change every 48 months

| POWER STEERING Capacity: 0-0 liter (Between min and max.) | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |
| Check every 12 months/ 30000 km | | |

SAAB 9-5 9-5 2.0T (2010-2011)



| COOLING SYSTEM Capacity: 0-0 liter (Between min and max.) | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Coolant SP 15+ | Coolant SP 12 | | | |
| Check every 12 months/ 30000 km | | | | |

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.