SAAB 9-5 9-5 3.0 V6 T (2000-2001)



ENGINE B308i Capacity: 5 liter (Initial fill), Capacity: 4,5 liter (Service fill)				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Emperol 10W-40	Bi-Turbo 15W-40			
Change every 20000 km/ 12 months				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Asyntho 5W-30				
Change every 20000 km/ 12 months				

TRANSAXLE AUTOMATIC 4/1 Capacity: 3,2 liter		
use Normal	climate Moderate	
PRODUCT RECOMMENDATION 1	Moderate	
ATF Almirol		

Check every 20000 km/ 12 months, change every 100000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,9 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 40000 km/48 months				

Change every 40000 km/48 months

POWER STEERING Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 20000 km/ 12 months	

SAAB 9-5 9-5 3.0 V6 T (2000-2001)



COOLING SYSTEM Capacity: 7,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 20000 km/ 12 months, change every 80000 k	m/36 months

Check every 20000 km/12 months, change every 80000 km/36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.