SAAB 900 900I 2.1 16V (1990-1991)



ENGINE B212i Capacity: 4 liter, Filter capacity: 0,3 liter		
USE CLIMATE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Change every 20000 km/ 12 months

DIFFERENTIAL FROM AUTOMAT Capacity: 1,25 liter	TIC	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 20000 km/ 12 months		

TRANSAXLE MANUAL 5/1 Capacity: 3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		
Chook over 20000 km/12 months			

Check every 20000 km/ 12 months

TRANSMISSION AUTOMATIC Borg Warner 37 3/1 Capacity: 3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	
Change every 40000 km/ 48 months	· ·

HYDRAULIC BRAKE/CLUTCH SYSTI Capacity: 0,58 liter	EM	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 40000 km/ 48 months		

SAAB 900 900I 2.1 16V (1990-1991)



POWER STEERING

Capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 36 months	·

AIRCONDITIONING COMPRESSOR Sankyo SD508/SeikoSeiki SS170 Capacity: 170-175 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 0,95-1,15 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.