

SAAB 9000 9000I 2.0 (1992-1993)**ENGINE B201i**

Capacity: 4,2 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Emperol 5W-40*Change every 20000 km/ 12 months*

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 5000 km/ 12 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 5000 km/ 12 months*

USE	CLIMATE
First change only	Arctic

PRODUCT RECOMMENDATION 1

Emperol 5W-40*Change every 5000 km/ 12 months*

SAAB 9000 9000I 2.0 (1992-1993)**TRANSAXLE AUTOMATIC ZF 4/1**

Capacity: 8,4 liter (Dry fill), Capacity: 3,3-3,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 40000 km/ 48 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Change every 30000 km/ 24 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

Check every 20000 km/ 12 months

USE	CLIMATE
Normal, first inspection	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

*Check every 24 months/ 30000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 40000 km/ 48 months***POWER STEERING**

Capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SAAB 9000 9000I 2.0 (1992-1993)**COOLING SYSTEM**

Capacity: 9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF***Change every 60000 km/ 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.