

# SAAB 9000 9000I 2.3 AERO (147 KW) (1992-1997)

**ENGINE**

Capacity: 5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Emperol 5W-40***Change every 20000 km/ 12 months*

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
First change only	Arctic

PRODUCT RECOMMENDATION 1

**Emperol 5W-40***Check every 3000 km, change every 10000 km/ 12 months*

# SAAB 9000 9000I 2.3 AERO (147 KW) (1992-1997)



## TRANSAXLE AUTOMATIC ZF 4/1

Capacity: 8,4 liter (Dry fill), Capacity: 3,3-3,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

Change every 40000 km/ 48 months

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Change every 40000 km/ 48 months

## POWER STEERING

Capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## COOLING SYSTEM

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

Change every 90000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.