## SCION (USA / CAN) XD XD 1.8 (USA) ZSP110 (2014-2014)



ENGINE 2ZR-FE Capacity: 4,7 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Presteza MSP 0W-20				
Change every 10000 miles/ 12 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
Presteza MSP 0W-20				
Change every 5000 miles/ 6 months				

TRANSAXLE AUTOMATIC U341E 4/1 Capacity: 6,5 liter (Dry fill), Capacity: 2,5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 30000 miles/ 36 months				

TRANSAXLE MANUAL 5/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 30000 miles/ 36 mont	hs	'

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check every 5000 miles/ 6 months			

PRODUCT RECOMMENDATION

## SCION (USA / CAN) XD XD 1.8 (USA) ZSP110 (2014-2014)



COOLING SYSTEM Capacity: 4,9 liter (with automatic transmission), Capacity: 5 liter (with manual transmission)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months				
USE		CLIMATE		
First change only		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				
Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.