

PRODUCT RECOMMENDATION

SEAT (EU) EXEO 3R EXEO 2.0 TDI (88 KW) (2008-2011)



ENGINE CAGC

Capacity: 4,3 liter

| USE | CLIMATE |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-----------------------------|
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 |

Change every 30000 km/ 24 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-----------------------------|
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 |

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 01X 6/1

Capacity: 3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Gear 5015 | |

Check every 48 months/ 60000 km

HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|----------------------------------|--|
| Drauliquid-LV Super DOT 4 | |

Change every 24 months

POWER STEERING

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Fluid 3013 | |

Check every 48 months/ 60000 km

SEAT (EU) EXEO 3R EXEO 2.0 TDI (88 KW) (2008-2011)

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.