SKODA SUPERB 3U SUPERB 2.5 TDI (120 KW) (2003-2005)



| ENGINE BDG Capacity: 5,4 liter | | |
|-----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Specialsynth MSP 5W-40 |
| Change every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Emperol 5W-40 | | |
| Change every 15000 km/ 12 months | | |

 DIFFERENTIAL FROM AUTOMATIC Capacity: 0,75 liter
 CLIMATE

 USE
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2

 SP Gear 1011
 Syngear TDL 75W-90

Check every 60000 km

| TRANSAXLE MANUAL 0A2 6/1 Capacity: 3,2 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |

Check every 15000 km/ 12 months

| TRANSMISSION AUTOMATIC 01V 5/1 Capacity: 9 liter (Initial fill), Capacity: 2,6-3 liter (Service fill) | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Matic 4026 | SP Matic 2032 | | |
| Check every 60000 km | | | |

SKODA SUPERB 3U SUPERB 2.5 TDI (120 KW) (2003-2005)



| HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| | |

Check every 15000 km/ 12 months, change every 24 months

| POWER STEERING Capacity: 1 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3013 | |
| | |

Check every 60000 km

| COOLING SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 12 EVO | | |
| Check every 15000 km/ 12 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.