

SKODA SUPERB II 3T SUPERB II 2.0 TDI (103 KW) (2008-2010)



ENGINE BKD, BMP
Capacity: 4,3 liter

USE

Extended drain (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30*Change every 30000 km/ 24 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30*Change every 15000 km/ 12 months*

TRANSAXLE MANUAL 02Q 6/1
Capacity: 2,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015*Check every 48 months/ 60000 km*

TRANSAXLE SEMI-AUTOMATIC DSG 02E (DQ250) 6/1
Capacity: 7,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Change every 60000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Check every 48 months/ 60000 km*

SKODA SUPERB II 3T SUPERB II 2.0 TDI (103 KW) (2008-2010)



POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 8,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.