SKODA YETI 5L YETI 1.6 MPI (81 KW) (2014-2018)



| ENGINE CWVA Capacity: 4,3 liter (Dry fill), Capacity: 4 liter (Service fill) | | | | |
|--|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Helar 0W-40 | Emperol 5W-40 | Asyntho 5W-30 | | |

Change every 15000 km/ 12 months

| TRANSAXLE AUTOMATIC 09G 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill) | | | |
|--|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| SP Matic 4036 | | | |
| Check every 60000 km | ' | | |

| TRANSAXLE MANUAL 0AH 5/1 Capacity: 2,2 liter | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 1081 | SP Gear 5015 | | |
| 01 1 40 41 / 00000 1 | ' | ' | |

Check every 48 months/ 60000 km

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 1-1,15 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| Check every 30000 km/24 months, change every 24 month | s |

| COOLING SYSTEM Capacity: 0-0 liter (Between min and max.) | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 12 EVO | |
| Check every 48 months/ 60000 km | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

SKODA YETI 5L YETI 1.6 MPI (81 KW) (2014-2018)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.