

SUBARU (EU) LEGACY / OUTBACK BM, BR LEGACY / OUTBACK 3.6R (2009-2010)

**ENGINE EZ36D**

Capacity: 7,8 liter (Dry fill), Capacity: 6,5 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Helar MSP+ 5W-40

Change every 5000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Helar MSP+ 5W-40

*Change every 15000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

*Check every 30000 km/ 24 months, change every 60000 km/ 48 months***DIFFERENTIAL REAR**

Capacity: 0,8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

SUBARU (EU) LEGACY / OUTBACK BM, BR LEGACY / OUTBACK 3.6R (2009-2010)

**TRANSAXLE AUTOMATIC 5/1**

Capacity: 9,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Check every 30000 km/ 24 months, change every 60000 km/ 48 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 30000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 15000 km/ 12 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 24 months/ 30000 km*

SUBARU (EU) LEGACY / OUTBACK BM, BR LEGACY / OUTBACK 3.6R (2009-2010)

**POWER STEERING**

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 24 months/ 30000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 6,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 120000 km/ 72 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 220000 km/ 132 months

AIRCONDITIONING COMPRESSOR R-134a

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 400-450 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.