

# SUZUKI BALENO SY BALENO 1.3 (2001-2002)

**ENGINE G13BB**

Capacity: 3,3 liter, Filter capacity: 0,2 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC 3/1**

Capacity: 4,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol***Check every 30000 km/ 24 months, change every 165000 km***TRANSAXLE AUTOMATIC 4/1**

Capacity: 5,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol***Check every 30000 km/ 24 months, change every 165000 km***TRANSAXLE MANUAL 5/1**

Capacity: 2,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**SP Gear 1081**

## PRODUCT RECOMMENDATION 3

**SP Gear 5015***Check every 15000 km/ 12 months, change every 45000 km*

# SUZUKI BALENO SY BALENO 1.3 (2001-2002)



## HYDRAULIC BRAKE SYSTEM ABS AS OPTION

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 15000 km/ 12 months, change every 24 months

## POWER STEERING AS OPTION

Capacity: 0,8 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Check every 15000 km/ 12 months

## COOLING SYSTEM

Capacity: 4,15 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

Check every 15000 km/ 12 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.