SUZUKI IGNIS IGNIS 1.3 RM413 (2003-2008)



ENGINE M 13A Capacity: 4,1 liter, Filter capacity: 0,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 5000 km/ 4 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40
Change every 5000 km/ 4 months		
TRANSAXLE AUTOMATIC 4/1 Capacity: 4,3 liter		

	1	· · · · · · · · · · · · · · · · · · ·
SP Matic 2032	ATF Almirol	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
Capacity: 4,3 liter		

Check every 30000 km/24 months, change every 165000 km

SUZUKI IGNIS IGNIS 1.3 RM413 (2003-2008)



TRANSAXLE MANUAL 5/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
Change every 45000 km/ 36 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
Check every 15000 km/ 12 months	·	

HYDRAULIC BRAKE SYSTEM ABS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 30000 km/ 24 months	·	

POWER STEERING Capacity: 0,8 liter		
use Normal		сымате Moderate
Normai		MODELAIE
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

COOLING SYSTEM Capacity: 4,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 45000 km/ 36 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.