

# SUZUKI SWIFT AZ SWIFT 1.3 DIESEL DPF AZG413D (2010-2014)



**ENGINE D13A**  
Capacity: 3,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|-----------------------------|---------------------------|--------------------------|
| <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> |

*Change every 6 months*

| USE            | CLIMATE  |
|----------------|----------|
| Flexible (max) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|-----------------------------|---------------------------|--------------------------|
| <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> |

*Change every 12 months*

**TRANSAXLE MANUAL 5/1**  
Capacity: 2,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
|--------------------------|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

*Change every 45000 km/ 36 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
|--------------------------|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

*Change every 30000 km/ 24 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
|--------------------------|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 15000 km/ 12 months*

**HYDRAULIC BRAKE SYSTEM ABS**  
Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |  |
|----------------------------------|---------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |  |

*Change every 30000 km/ 24 months*

# SUZUKI SWIFT AZ SWIFT 1.3 DIESEL DPF AZG413D (2010-2014)



## HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 24 months/ 30000 km*

## COOLING SYSTEM

Capacity: 6,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Change every 75000 km/ 48 months*

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Change every 150000 km/ 96 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

PRODUCT RECOMMENDATION 2

**Coolant -38 Organic NF***Change every 45000 km/ 36 months*

## AIRCONDITIONING COMPRESSOR

Capacity: 105-135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 350-390 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*