TOYOTA (EU) AURIS E15 AURIS 1.3 16V VVT-I (2009-2013)



ENGINE 1NR-FE Capacity: 3,9 liter (Dry fill), Capacity: 3,4 liter (Service fill), Filter capacity: 0,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 7500 km/ 6 months		

TRANSAXLE MANUAL EC60 6/1 Capacity: 2,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		
Check every 18 months/60000 km			

Check every 48 months/ 60000 km

USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

Change every 60000 km/ 48 months

HYDRAULIC BRAKE SYSTEM ABS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 30000 km/ 24 months	

TOYOTA (EU) AURIS E15 AURIS 1.3 16V VVT-I (2009-2013)



HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 30000 km/24 months		

COOLING SYSTEM Capacity: 4,7 liter, Capacity: 5,7 liter (with exhaust recirculation system)			
USE	, 	CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 30000 km, change every 90000 km			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			

Check every 30000 km, change every 150000 km

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 30 CM3

Coolant SP 14+

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 410-470 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.