

TOYOTA (EU) AURIS E18 AURIS 1.6 VVT-I (2013-2016)

**ENGINE 1ZR-FAE**

Capacity: 4,7 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30

Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30

*Change every 7500 km/ 6 months***TRANSAXLE CVT K311 1/1**

Capacity: 7,64 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4016		

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4016		

*Check every 45000 km/ 36 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL EC60 6/1**

Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

Change every 60000 km/ 48 months

TOYOTA (EU) AURIS E18 AURIS 1.6 VVT-I (2013-2016)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 30000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 30000 km/ 24 months

COOLING SYSTEM

Capacity: 5,8 liter (with CVT), Capacity: 5,6 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 90000 km

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 150000 km

AIRCONDITIONING COMPRESSOR R-1234yf

Capacity: 70 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 70 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-1234yf

Capacity: 370-430 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

TOYOTA (EU) AURIS E18 AURIS 1.6 VVT-I (2013-2016)



AIRCONDITIONING SYSTEM R-134a

Capacity: 400-500 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.