

# TOYOTA (EU) AURIS E18 AURIS 1.8 HYBRID (2013-2018)

**ENGINE 2ZR-FXE**

Capacity: 4,7 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,3 liter

| USE       | CLIMATE  |
|-----------|----------|
| Preferred | Moderate |

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 15000 km/ 12 months*

| USE               | CLIMATE  |
|-------------------|----------|
| Severe, preferred | Moderate |

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 7500 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

PRODUCT RECOMMENDATION 2

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 3

**Xedoz FE 5W-30***Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

PRODUCT RECOMMENDATION 2

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 3

**Xedoz FE 5W-30***Change every 7500 km/ 6 months***TRANSAXLE CVT P410 1/1**

Capacity: 3,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 48 months/ 60000 km*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 45000 km/ 36 months, change every 90000 km/ 72 months*

# TOYOTA (EU) AURIS E18 AURIS 1.8 HYBRID (2013-2018)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Change every 30000 km/ 24 months

## COOLING SYSTEM COMBUSTION ENGINE

Capacity: 6,3 liter, Capacity: 7 liter (+ heater)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 30000 km, change every 90000 km

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| First change only        |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 30000 km, change every 150000 km

## COOLING SYSTEM ELECTRIC DRIVE

Capacity: 2,1 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 30000 km, change every 90000 km

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| First change only        |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 30000 km, change every 150000 km

## AIRCONDITIONING COMPRESSOR

Capacity: 130-145 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

# TOYOTA (EU) AURIS E18 AURIS 1.8 HYBRID (2013-2018)



**AIRCONDITIONING SYSTEM R-1234yf**

Capacity: 470-530 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM R-134a**

Capacity: 420-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*