

# TOYOTA (EU) AVENSIS T25 AVENSIS 1.8

## 16V VVT-I (2003-2006)

**ENGINE 1ZZ-FE**

Capacity: 4,2 liter (Dry fill), Capacity: 3,7 liter (Service fill), Filter capacity: 0,2 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Change every 15000 km/ 12 months*

| USE    | CLIMATE       |
|--------|---------------|
| Severe | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 7500 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC U341E 4/1**

Capacity: 6,9 liter (Dry fill), Capacity: 3 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 45000 km/ 36 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 45000 km/ 36 months, change every 90000 km/ 72 months*

# TOYOTA (EU) AVENSIS T25 AVENSIS 1.8 16V VVT-I (2003-2006)



## TRANSAXLE MANUAL C250 5/1

Capacity: 1,9 liter

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Normal                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Check every 48 months/ 60000 km

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Severe                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Change every 60000 km/ 48 months

## HYDRAULIC BRAKE SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Change every 30000 km/ 24 months

## HYDRAULIC CLUTCH SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Check every 24 months/ 30000 km

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# TOYOTA (EU) AVENSIS T25 AVENSIS 1.8 16V VVT-I (2003-2006)

**COOLING SYSTEM**

Capacity: 5,7-5,8 liter (Left hand drive), Capacity: 5,8-5,9 liter (Right hand drive)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 30000 km, change every 90000 km

| USE               | CLIMATE  |
|-------------------|----------|
| First change only | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 30000 km, change every 150000 km

**AIRCONDITIONING COMPRESSOR R-134a**

Capacity: 105 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM R-134a**

Capacity: 410-470 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*