TOYOTA (EU) COROLLA VERSO E12 COROLLA VERSO 2.0 D4-D (2002-2003)



SE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Asyntho 5W-30	PRODUCT RECOMMENDATION 2 Emperol 10W-40	PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40
Change every 15000 km/ 12 months		
use Normal		climate Cold
PRODUCT RECOMMENDATION 1 Duranza LSP 5W-30		
Change every 15000 km/ 12 months	'	
use Severe		сымате Mediterranean
PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
use Severe		climate Moderate
PRODUCT RECOMMENDATION 1 Asyntho 5W-30	PRODUCT RECOMMENDATION 2 Emperol 10W-40	PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40
Change every 7500 km/ 6 months		
use Severe		climate Cold
PRODUCT RECOMMENDATION 1 Duranza LSP 5W-30		
Change every 7500 km/ 6 months	1	1

TOYOTA (EU) COROLLA VERSO E12 COROLLA VERSO 2.0 D4-D (2002-2003)



TRANSAXLE MANUAL E351 5/1 Capacity: 2,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90	
Check every 48 months/ 60000 km			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90	
Change every 60000 km/ 48 month	S	1	

HYDRAULIC BRAKE SYSTEM ABS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 30000 km/24 months	·	

HYDRAULIC CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 24 months/ 30000 km	'	

POWER STEERING				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
SP Matic 2032	ATF Almirol	ATF Dexron II-D		
Check every 24 months/ 30000 km	'			

PRODUCT RECOMMENDATION

TOYOTA (EU) COROLLA VERSO E12 COROLLA VERSO 2.0 D4-D (2002-2003)



COOLING SYSTEM Capacity: 7,4-7,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Change every 30000 km/ 24 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Change every 60000 km/ 36 months		

AIRCONDITIONING COMPRESSOR R-134a Capacity: 70 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 500-560 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.