

TOYOTA (EU) PRIUS + W4 PRIUS+ W4(2011-2019)

**ENGINE 2ZR-FXE**

Capacity: 4,7 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe, preferred	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 7500 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Xedoz FE 5W-30*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 3

Xedoz FE 5W-30*Change every 7500 km/ 6 months***TRANSAXLE CVT P410 1/1**

Capacity: 3,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 45000 km/ 36 months, change every 90000 km/ 72 months*

TOYOTA (EU) PRIUS + W4 PRIUS+ W4(2011-2019)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 30000 km/ 24 months

COOLING SYSTEM

Capacity: 6,5 liter, Capacity: 6,9 liter (+ exhaust heat recovery system)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 90000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 150000 km

COOLING SYSTEM INVERTER

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 90000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 240000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.