TOYOTA (EU) PRIUS W2 PRIUS THSD W2



(2003-2006)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Bi-Turbo 15W-40	
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Bi-Turbo 15W-40	
Change every 7500 km/ 6 months	•	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Check every 45000 km/ 36 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

Capacity: 3,6 liter

HYDRAULIC BRAKE SYSTEM ABS



IOYOTA (EU)	PRIUS W2	PRIUS	IHSD	W2
(2003-2006)				

Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check every 15000 km/ 12 months, change every 30000 km/ 24 months			
COOLING SYSTEM COMBUSTION ENGINEERS Capacity: 8,6 liter	NE		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 30000 km, change every 90000 km			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			

Capacity: 2,7 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 30000 km, change every 90000 km			
USE	CLIMATE		
First change only	Moderate		

Check every 30000 km, change every 150000 km

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km, change every 150000 km

COOLING SYSTEM ELECTRIC DRIVE

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.