TOYOTA (EU) RAV4 A3 RAV4 2.0 16V VVT-I 4WD (2009-2013)



SE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months	3	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30
Change every 15000 km/ 12 months	3	
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30
Change every 7500 km/6 months		
DIFFERENTIAL REAR		
Capacity: 0,45-0,55 liter		
USE Normal		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

TOYOTA (EU) RAV4 A3 RAV4 2.0 16V VVT-I 4WD (2009-2013)



TRANSAXLE CVT K111F 1/1 Capacity: 9 liter (Dry fill), Capacity: 2,1 liter (Service fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4016		
Check every 48 months/ 60000 km		
USE	CLIMATE	
Severe	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4016		
Check every 45000 km/ 36 months, char	nge every 90000 km/ 72 months	

TRANSAXLE MANUAL EB61F 6/Capacity: 2,4 liter	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 48 months/ 60000 km		
USE		CLIMATE

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Change every 60000 km/ 48 months	S	

TRANSFERBOX GF1A Capacity: 0,45 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Change every 30000 km/ 48 months

PRODUCT RECOMMENDATION

TOYOTA (EU) RAV4 A3 RAV4 2.0 16V VVT-I 4WD (2009-2013)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 30000 km/24 months	

HYDRAULIC CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 30000 km/ 24 months	·

COOLING SYSTEM
Capacity: 6 liter (with CVT transmission), Capacity: 5,8 liter (with manual transmission)

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant SP 14+

USE CLIMATE
First change only Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km, change every 150000 km

Check every 30000 km, change every 90000 km

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 145 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 400-460 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.