Change every 60000 km/48 months

## **TOYOTA (EU) RAV4 A4 RAV4 2.0 D-4D 2WD** (2013-2015)



ENGINE 1AD-FTV Capacity: 6,7 liter (Dry fill), Capacity: 5,9 l	iter (Service fill), Filter capacity: 0,4 liter	
USE		CLIMATE
Normal, fuel sulfur level < 50 ppm		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe, fuel sulfur level < 50 ppm		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30
Change every 7500 km/ 6 months		

TRANSAXLE MANUAL EA64 6/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 48 months/ 60000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 30000 km/ 24 months	

## **TOYOTA (EU) RAV4 A4 RAV4 2.0 D-4D 2WD** (2013-2015)



HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 30000 km/24 months		

COOLING SYSTEM Capacity: 7,3-7,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km, change every 9	0000 km	

Check every 30000 km, change every 90000 km

USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 30000 km, change every 150000 km

## **AIRCONDITIONING COMPRESSOR** R-134a

Capacity: 70 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## **AIRCONDITIONING SYSTEM** R-134a

Capacity: 470-530 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.