

# TOYOTA (EU) STARLET STARLET 1.3i (1990-1996)

**ENGINE 2E-E**

Capacity: 3,2 liter, Filter capacity: 0,3 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Bi-Turbo 15W-40</b>   | <b>Bi-Turbo 20W-50</b>   | <b>HDX 20W-50</b>        |

*Change every 10000 km/ 6 months*

| USE                      |                                  | CLIMATE  |
|--------------------------|----------------------------------|----------|
| Normal                   |                                  | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2         |          |
| <b>Emperol 10W-40</b>    | <b>Classic Racing Oil 15W-50</b> |          |

*Change every 10000 km/ 6 months*

| USE                      |  | CLIMATE |
|--------------------------|--|---------|
| Normal                   |  | Cold    |
| PRODUCT RECOMMENDATION 1 |  |         |
| <b>Asyntho 5W-30</b>     |  |         |

*Change every 10000 km/ 6 months*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Severe                   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Bi-Turbo 15W-40</b>   | <b>Bi-Turbo 20W-50</b>   | <b>HDX 20W-50</b>        |

*Change every 5000 km/ 3 months*

| USE                      |                                  | CLIMATE  |
|--------------------------|----------------------------------|----------|
| Severe                   |                                  | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2         |          |
| <b>Emperol 10W-40</b>    | <b>Classic Racing Oil 15W-50</b> |          |

*Change every 5000 km/ 3 months*

| USE                      |  | CLIMATE |
|--------------------------|--|---------|
| Severe                   |  | Cold    |
| PRODUCT RECOMMENDATION 1 |  |         |
| <b>Asyntho 5W-30</b>     |  |         |

*Change every 5000 km/ 3 months*

# TOYOTA (EU) STARLET STARLET 1.3i (1990-1996)



## DIFFERENTIAL FROM AUTOMATIC

Capacity: 1,4 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 20000 km, change every 40000 km/ 24 months

## TRANSAXLE MANUAL 5/1

Capacity: 2,4 liter

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Normal                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Check every 20000 km/ 12 months, change every 80000 km/ 48 months

## TRANSMISSION AUTOMATIC 3/1

Capacity: 2,2 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 20000 km, change every 40000 km/ 24 months

## HYDRAULIC BRAKE SYSTEM

Capacity: 1,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 1 months, change every 40000 km/ 24 months

## HYDRAULIC CLUTCH SYSTEM

Capacity: 1,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 1 months, change every 40000 km/ 24 months

# TOYOTA (EU) STARLET STARLET 1.3i (1990-1996)



## POWER STEERING

Capacity: 1,4 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 20000 km/ 12 months

## GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 40000 km/ 48 months

## COOLING SYSTEM

Capacity: 4,8 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

Check every 1 months, change every 40000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.