

# TOYOTA (EU) VERSO R2 VERSO 2.2 D-4D-CAT (130 KW) (2009-2015)

**ENGINE 2AD-FHV**

Capacity: 6,7 liter (Dry fill), Capacity: 5,9 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza MSP 0W-30</b>	<b>Presteza MSP 0W-30</b>	<b>Avanza MSP 0W-30</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza MSP 0W-30</b>	<b>Presteza MSP 0W-30</b>	<b>Avanza MSP 0W-30</b>

*Change every 7500 km/ 6 months***TRANSAXLE MANUAL EA62 6/1**

Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>	

*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>	

*Change every 60000 km/ 48 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 30000 km/ 24 months*

# TOYOTA (EU) VERSO R2 VERSO 2.2 D-4D-CAT (130 KW) (2009-2015)



## HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 24 months/ 30000 km

## COOLING SYSTEM

Capacity: 7,4-7,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

Check every 30000 km, change every 90000 km

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

Check every 30000 km, change every 150000 km

## AIRCONDITIONING COMPRESSOR R-134a

Capacity: 50 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM R-134a

Capacity: 410-470 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*