TOYOTA (USA / CAN) CAMRY XV30 CAMRY 3.0 V6 (USA) MCV30 (2006-2006)



ENGINE 1MZ-FE Capacity: 5,5 liter (Dry fill), Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Presteza MSP 5W-30			
Chapter over 5000 miles (6 months			

Change every 5000 miles/ 6 months

TRANSAXLE AUTOMATIC U151E 5/1 Capacity: 3,5 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 30000 miles/ 36 months	-

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Charles war 20000 miles / 20 menths, charge avery 20000 miles / 70 menths		

Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check even 5000 miles 6 months			

Check every 5000 miles/ 6 months

Charles war E000 miles (6 months		
SP Matic 2032	ATF Almirol	ATF Dexron II-D
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
POWER STEERING		

Check every 5000 miles/ 6 months

TOYOTA (USA / CAN) CAMRY XV30 CAMRY 3.0 V6 (USA) MCV30 (2006-2006)



COOLING SYSTEM Capacity: 9,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 15000 miles/ 18 months, cha	nge every 100000 miles/ 120 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.