

PRODUCT RECOMMENDATION

# TOYOTA (USA / CAN) HIGHLANDER XU40 HIGHLANDER 3.5 V6 24V 2WD (USA) GSU40 (2008-2010)



## ENGINE 2GR-FE

Capacity: 6,8-7,1 liter (Dry fill), Capacity: 6,1 liter (Service fill), Filter capacity: 0,4 liter

### USE

Normal

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

*Change every 5000 miles/ 6 months*

### USE

with towing package

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

*Change every 5000 miles/ 6 months*

## TRANSAXLE AUTOMATIC U151E 5/1

Capacity: 8,8 liter (Dry fill), Capacity: 3,5 liter (Service fill)

### USE

Normal

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Check every 30000 miles/ 36 months*

### USE

Severe

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

### USE

Normal

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

*Check every 5000 miles/ 6 months*

# TOYOTA (USA / CAN) HIGHLANDER XU40

## HIGHLANDER 3.5 V6 24V 2WD (USA) GSU40

### (2008-2010)

**COOLING SYSTEM**

Capacity: 8,8 liter, Capacity: 11 liter (+ rear heater), Capacity: 9,5 liter (with towing package), Capacity: 11,7 liter (with towing package + rear heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

*Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

*Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*