

TOYOTA (USA / CAN) PRIUS XW30 PRIUS PHV (USA) ZVW35 (2011-2015)

**ENGINE 2ZR-FXE**

Capacity: 4,7 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 10000 miles/ 12 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 5000 miles/ 6 months***TRANSAXLE CVT P410 1/1**

Capacity: 3,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 30000 miles/ 36 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 5000 miles/ 6 months*

TOYOTA (USA / CAN) PRIUS XW30 PRIUS PHV (USA) ZVW35 (2011-2015)

**COOLING SYSTEM**

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

COOLING SYSTEM ELECTRIC DRIVE

Capacity: 2,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.