PRODUCT RECOMMENDATION

# TOYOTA (USA / CAN) RAV4 XA10 RAV4 2.0 16V 2WD (USA) SXA15/16 (1999-2000)

## ENGINE 3S-FE
Capacity: 4,5 liter (Dry fill), Capacity: 4,1 liter (Service fill), Filter capacity: 0,2 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Asyntho 5W-30** | | |

*Change every 7500 miles/ 6 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Asyntho 5W-30** | | |

*Change every 5000 miles/ 4 months*

## TRANSAXLE AUTOMATIC A247E 4/1
Capacity: 3,3 liter (Service fill)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **SP Matic 2032** | **ATF Almirol** | **ATF Dexron II-D** |

*Check every 15000 miles/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **SP Matic 2032** | **ATF Almirol** | **ATF Dexron II-D** |

*Change every 15000 miles/ 12 months*

## TRANSAXLE MANUAL 5/1
Capacity: 3,9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **SP Gear 1011** | **Syngear TDL 75W-90** | **Syngear 75W-90** |

*Check every 30000 miles/ 24 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **SP Gear 1011** | **Syngear TDL 75W-90** | **Syngear 75W-90** |

*Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# TOYOTA (USA / CAN) RAV4 XA10 RAV4 2.0 16V 2WD (USA) SXA15/16 (1999-2000)

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Drauliquid DOT 3** | | |

*Check every 15000 miles/ 12 months*

## POWER STEERING

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **SP Matic 2032** | **ATF Almirol** | **ATF Dexron II-D** |

*Check every 15000 miles/ 12 months*

## COOLING SYSTEM

Capacity: 7,7 liter (with automatic transmission), Capacity: 8 liter (with manual transmission)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Coolant SP 12 EVO** | | |

*Check every 15000 miles/ 12 months, change every 30000 miles/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367