PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) SEQUOIA SEQUOIA 4.7 V8 32V 2WD (USA) UCK35 (2004-2005)

ENGINE 2UZ-FE
Capacity: 7,1 liter (Dry fill), Capacity: 6,2 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Change every 5000 miles/ 6 months

DIFFERENTIAL REAR
Capacity: 3,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Check every 15000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Check every 15000 miles/ 18 months, change every 30000 miles/ 36 months

TRANSMISSION AUTOMATIC A750E 5/1
Capacity: 10,8 liter (Dry fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 30000 miles/ 36 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 30000 miles/ 36 months, change every 60000 miles/ 72 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOYOTA (USA / CAN) SEQUOIA SEQUOIA 4.7 V8 32V 2WD (USA) UCK35 (2004-2005)

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 miles/ 6 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Check every 5000 miles/ 6 months

COOLING SYSTEM

Capacity: 12,8 liter, Capacity: 14,5 liter (+ rear heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367