## **TOYOTA (USA / CAN) T100 T100 3.4 V6 2WD** (USA) VCK11 (1996-1996)



ENGINE 5VZ-FE Capacity: 5,9 liter (Dry fill), Capacity: 5,2 lit	er (Service fill), Filter capacity: 0,3 liter	
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Asyntho 5W-30		

DIFFERENTIAL REAR Capacity: 2,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

TRANSMISSION AUTOMATIC A340E 4/1 Capacity: 7,2 liter (Dry fill), Capacity: 1,6 liter (Service fill)		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

TRANSMISSION MANUAL 5/1 Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

## **TOYOTA (USA / CAN) T100 T100 3.4 V6 2WD** (USA) VCK11 (1996-1996)



HYDRAULIC CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

<b>COOLING SYSTEM</b> Capacity: 9,9 liter (with automatic transmis	on), Capacity: 10 liter (with manual transmission)
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.